

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Biresin® CH122-9 Hardener (B)



Revision Date 08.12.2014

Version 3.0

Print Date 08.12.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Biresin® CH122-9 Hardener (B)

1.2 Relevant identified uses of the substance or mixture and uses advised against

At present there is no complete information available on identified uses. When the data becomes available, it will be integrated into the safety data sheet.

Product use : Composites system.

1.3 Details of the supplier of the safety data sheet

Company : Sika Deutschland GmbH
Kornwestheimer Str. 103-107
70439 Stuttgart
Telephone : +4971180090
E-mail address : EHS@de.sika.com

1.4 Emergency telephone number

Emergency telephone number : 0173-6774799 Out of office hours only
EHS@de.sika.com

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity , Category 4	H302: Harmful if swallowed.
Acute toxicity , Category 2	H330: Fatal if inhaled.
Acute toxicity , Category 3	H311: Toxic in contact with skin.
Skin corrosion , Category 1B	H314: Causes severe skin burns and eye damage.
Chronic aquatic toxicity , Category 2	H411: Toxic to aquatic life with long lasting effects.

Classification (67/548/EEC, 1999/45/EC)

Toxic	R23/24: Toxic by inhalation and in contact with skin.
Corrosive	R35: Causes severe burns.
Harmful	R22: Harmful if swallowed.
Dangerous for the environment	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Biresin® CH122-9 Hardener (B)



Revision Date 08.12.2014

Version 3.0

Print Date 08.12.2014

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H330	Fatal if inhaled.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

:

Prevention:

P260

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/ physician.

Storage:

P403 + P233

Store in a well-ventilated place. Keep container tightly closed.

Hazardous components which must be listed on the label:

- 229-962-1 2,2'-dimethyl-4,4'-methylenebis(cyclohexylamine)

Additional Labelling:

Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).
This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Biresin® CH122-9 Hardener (B)



Revision Date 08.12.2014

Version 3.0

Print Date 08.12.2014

Hazardous components

Chemical Name CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
2,2'-dimethyl- 4,4'-methylenebis(cyclohexylamine) 6864-37-5 229-962-1 01-2119497829-12-XXXX	T; R23/24 C; R35 Xn; R22 N; R51/53	Acute Tox.2; H330 Acute Tox.3; H310 Acute Tox.4; H302 Skin Corr.1B; H314 Aquatic Chronic2; H411	>= 50 - <= 100

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
- If inhaled : Call a physician or poison control centre immediately.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
Take victim immediately to hospital.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Gastrointestinal discomfort
Respiratory disorder
Headache
Dermatitis
Skin disorders
See Section 11 for more detailed information on health effects

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Biresin® CH122-9 Hardener (B)



Revision Date 08.12.2014

Version 3.0

Print Date 08.12.2014

and symptoms.

Risks : Health injuries may be delayed.
corrosive effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Biresin® CH122-9 Hardener (B)



Revision Date 08.12.2014

Version 3.0

Print Date 08.12.2014

acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid exceeding of the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : Avoid contact with skin, eyes and clothing. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Prevent unauthorized access. Store in original container. Keep in a well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.
- Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Biresin® CH122-9 Hardener (B)



Revision Date 08.12.2014

Version 3.0

Print Date 08.12.2014

- | | |
|--------------------------|--|
| Eye protection | : Safety glasses with side-shields
Eye wash bottle with pure water
Wear eye/face protection. |
| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (0,4 mm),
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min. |
| Skin and body protection | : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work. |
| Respiratory protection | : No special measures required. |
- Environmental exposure controls**
- | | |
|----------------|--|
| General advice | : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities. |
|----------------|--|

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|------------------------------|---------------------|
| Appearance | : liquid |
| Colour | : blue |
| Odour | : amine-like |
| Odour Threshold | : No data available |
| Flash point | : ca. 173 °C |
| Autoignition temperature | : 275 °C |
| Lower explosion limit (Vol%) | : No data available |
| Upper explosion limit (Vol%) | : No data available |
| Flammability (solid, gas) | : No data available |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Biresin® CH122-9 Hardener (B)



Revision Date 08.12.2014

Version 3.0

Print Date 08.12.2014

Oxidizing properties	: No data available
Auto-ignition temperature	: No data available
pH	: ca. 11 at 20 °C
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: 347 °C
Vapour pressure	: No data available
Density	: ca. 0,95 g/cm ³ at 20 °C
Water solubility	: Note: insoluble
Partition coefficient: n-octanol/water	: No data available
Viscosity, dynamic	: ca. 140 mPa.s at 20 °C
Viscosity, kinematic	: > 20,5 mm ² /s at 40 °C
Relative vapour density	: No data available
Evaporation rate	: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Biresin® CH122-9 Hardener (B)



Revision Date 08.12.2014

Version 3.0

Print Date 08.12.2014

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

2,2'-dimethyl-4,4'-methylenebis(cyclohexylamine) :

Acute oral toxicity	: LD50 Oral rat: 320 - 460 mg/kg
Acute inhalation toxicity	: LC50 rat: 0,42 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	: LD50 Dermal rabbit: 200 - 400 mg/kg

Skin corrosion/irritation

Product

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Product

No data available

Respiratory or skin sensitisation

Product

No data available

Germ cell mutagenicity

Product

Mutagenicity : No data available

Carcinogenicity

Product

Carcinogenicity : No data available

Reproductive Toxicity/Fertility

Reproductive toxicity : No data available

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Biresin® CH122-9 Hardener (B)



Revision Date 08.12.2014

Version 3.0

Print Date 08.12.2014

No data available

Reproductive Toxicity/Development/Teratogenicity

Teratogenicity : No data available

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : In accordance with the EWC Waste Regulation the classification of waste is to be assigned to the jurisdiction of the origin of waste. Therefore, it is not possible to assign a particular

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Biresin® CH122-9 Hardener (B)



Revision Date 08.12.2014

Version 3.0

Print Date 08.12.2014

waste identification number.
Completely emptied packagings may be given for recycling.
Empty packaging may still contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.
Sika has agreed disposal contracts for all packaging which is brought into circulation in Germany.
For further details see www.sika.de

SECTION 14: Transport information

ADR

- 14.1 UN number : 2922
- 14.2 Description of the goods : CORROSIVE LIQUID, TOXIC, N.O.S.
(2,2'-dimethyl-4,4'methylenebis(cyclohexylamine))
- 14.3 Class : 8
- 14.4 Packing group : II
- Classification Code : CT1
- Labels : 8 (6.1)
- Tunnel restriction code : (E)
- 14.5 Environmentally hazardous : yes

IATA

- 14.1 UN number : 2922
- 14.2 Description of the goods : Corrosive liquid, toxic, n.o.s.
(2,2'-dimethyl-4,4'methylenebis(cyclohexylamine))
- 14.3 Class : 8
- 14.4 Packing group : II
- Labels : 8 (6.1)
- 14.5 Environmentally hazardous : yes

IMDG

- 14.1 UN number : 2922
- 14.2 Description of the goods : CORROSIVE LIQUID, TOXIC, N.O.S.
(2,2'-dimethyl-4,4'methylenebis(cyclohexylamine))
- 14.3 Class : 8
- 14.4 Packing group : II
- Labels : 8 (6.1)
- EmS Number 1 : F-A
- EmS Number 2 : S-B
- 14.5 Marine pollutant : yes

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Biresin® CH122-9 Hardener (B)



Revision Date 08.12.2014

Version 3.0

Print Date 08.12.2014

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Labelling according to EC Directives (1999/45/EC)

Hazard pictograms :



Toxic



Dangerous for the environment

R-phrases(s)	:	R22	Harmful if swallowed.
		R23/24	Toxic by inhalation and in contact with skin.
		R35	Causes severe burns.
		R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
S-phrases(s)	:	S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
		S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
		S45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Hazardous components which must be listed on the label:

- 229-962-1 2,2'-dimethyl-4,4'-methylenebis(cyclohexylamine)

Special labelling of certain mixtures : Contains epoxy constituents. See information supplied by the manufacturer.

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : not applicable

REACH Information: All substances contained in our Products are
- preregistered or registered by our upstream suppliers, and/or
- preregistered or registered by us, and/or
- excluded from the regulation, and/or

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Biresin® CH122-9 Hardener (B)



Revision Date 08.12.2014

Version 3.0

Print Date 08.12.2014

- exempted from the registration.

Water contaminating class (Germany) : WGK 3 highly water endangering
List with water hazardous substances (Class 1 till 3) in
VwVwS
Gemäß VwVws vom 30.Juli 2005

VOC-CH (VOCV) : < 0,01 %
no VOC duties

VOC-EU (solvent) : < 0,01 %

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of R-Phrases

R22	Harmful if swallowed.
R23/24	Toxic by inhalation and in contact with skin.
R35	Causes severe burns.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Full text of H-Statements

H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H330	Fatal if inhaled.
H411	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	Acute toxicity
Aquatic Chronic	Chronic aquatic toxicity
Skin Corr.	Skin corrosion

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !